

2AL Aluminium Cylinders

Product offering

Calgaz has a range of three types of 2AL cylinders designed to meet your needs. The 2ALE and 2ALU are both approved for global use and vary only slightly in terms of height, appearance and weight. The 2ALR is our refillable cylinder version which again can only be supplied in the USA.

All cylinders have the universal C10 valve as standard and can be filled with both non-reactive and reactive gases.



*2ALU Picture

Characteristic				
	Contents	Pressure	Dimensions	Weight
2ALE	34 liters	35 bar (500 psi)	289 mm x 76 mm (11.4" x 3")	0.61 kg (1.3lb)
2ALR	60 liters	70 bar (1000 psi)	293 mm x 74 mm (11.6" x 3")	0.54 kg (1.2lb)
2ALU	34 liters	35 bar (500 psi)	289 mm x 76 mm (11.4" x 3")	0.44 kg (1lb)

Specifications				
	Approvals	Type	Cylinder Valve	Recommended Equipment
2ALE	Global	Non-Refillable	C10	Most commonly used regulators include 700 Series, DFR 2000 Series, or 4200 Trigger regulators.
2ALR	Only U.S.	Refillable	C10	
2ALU	Global	Non-Refillable	C10	



Contact Details

Americas

Global Headquarters

Houston, TX, USA
+1 713 624 8000

Customer Service and Manufacturing Facility

Cambridge, MD, USA
+1 800 638 1197

Europe, Middle East & Africa

Customer Service, Sales and Manufacturing Facility

Stoke-on-Trent, United
Kingdom
+44 1782 566897

Middle East Sales

Dubai, UAE
+971 56 131 2346

South East Asia & Australia

Customer Service and Distribution

Singapore
+65 62653788

China

Customer Service and Distribution

Shanghai
+86 21 6090 3711

info@calgaz.com

www.calgaz.com